

55% transmittance poly-crystal modules-28 cells
55%透光多晶组件—28片



结构参数

Mechanical Specifications

Parameter/参数	Value/数值
Cell Type/电池类型	Polycrystalline/多晶硅 (156mm*156mm)
Solar Cells/电池片数量[片]	28(4*7)
Length*Width*Thickness/长*宽*厚[mm]	1658*992*6
Weight/重量[Kg]	22.5
Front Glass/前板玻璃[mm]	2.5 (Low iron semi tempered coated glass/低铁压花半钢化镀膜玻璃)
Interlayer/中间层[mm]	EVA/POE/PVB
Back Glass/背板玻璃[mm]	2.5 (Float semi tempered glass/浮法半钢化玻璃)
Junction Box/接线盒	IP67 Rated, 2 by-pass diodes /2个旁路二极管, 满足IP67安全防护等级
Connector/连接器	Multi-Contact MC-4(or equivalent)/MC-4连接器 (或同类产品)
Transmittance/透光率[%]	55
Maximum Load Capacity/机械负载[Pa]	2400(风压)/5400(雪压)

电学性能

Electrical Characteristics

Parameter/参数		DP28-105	DP28-115	DP28-120	DP28-125	
STC : 光谱 AM1.5, 辐照度 1000W/m ² , 电 池温度25°C	Maximum Power at STC [Pmax]/标测下最大功率	[W]	105	115	120	125
	Open Circuit Voltage [Voc]/开路电压	[V]	17.30	17.50	17.80	18.00
	Short Circuit Current [Isc]/短路电流	[A]	8.42	8.47	8.50	8.55
	Voltage at Maximum Power point[Vm]/最大功率点电压	[V]	13.80	14.00	14.20	14.40
	Current at Maximum Power point[Im]/最大功率点电流	[A]	7.61	7.85	8.10	8.34
	Power Tolerance /功率偏差	[%]	0~+3%			
NOCT : 光谱 AM1.5, 辐照度 800W/m ² , 环 境温度20°C, 风 速1m/s	Module Efficiency/转换效率	[%]	6.3	6.6	6.9	7.2
	Maximum Power at NOCT [Pmax]/NOCT下最大功率	[W]	78	82	86	89
	Open Circuit Voltage [Voc]/开路电压	[V]	15.95	16.10	16.40	16.58
	Short Circuit Current [Isc]/短路电流	[A]	6.91	6.95	6.98	7.02
	Voltage at Maximum Power point[Vm]/最大功率点电压	[V]	12.47	12.65	12.85	13.04
	Current at Maximum Power point[Im]/最大功率点电流	[A]	6.26	6.45	6.67	6.83
Power Tolerance /功率偏差	[%]	0~+3%				

工作范围

Scope of Work

Parameter/参数	Unit / 单位	Value/数值
Maximum System Voltage /最大系统电压	[V]	1000 DC(IEC)或1500 DC(IEC)
Operating Temperature /工作温度范围	[°C]	-40~85
Nominal Operating Cell Temperature/额定电池工作温度	[°C]	45±3
Maximum rated current/最大保险丝额定电流	[A]	15

温度系数

Temperature Coefficients

Parameter/参数	Unit / 单位	Value/数值
Temperature Coefficient of Pmax/最大功率温度系数	[%/°C]	-0.42
Temperature Coefficient of Voc/开路电压温度系数	[%/°C]	-0.33
Temperature Coefficient of Isc/短路电流温度系数	[%/°C]	0.04


包装信息

Packaging information

Package Size	Container	20'GP	40'GP	40'HQ
1780×1120×1160mm	pieces for pallet	36	36	36
	pallets for Container	6	13	26
	pieces for Container	216	468	936

结构视图

Module Layout




总装图

Components

- Front Glass (2.5mm Low iron semi tempered coated glass)
- Encapsulant (EVA/POE/PVB)
- Cell Type (Mono crystalline 156mm×156mm)
- Encapsulant (EVA/POE/PVB)
- Back Glass (2.5mm Float semi tempered glass)

曲线图

Electrical curves



输出功率线性质保

业内领先的线性质保

认证标识

Certification

