

Datasheet	Growatt 33000 TL3-US	Growatt 36000 TL3-US	Growatt 40000 TL3-US
Input Data (DC)			
Max. usable DC power	33700W	36750W	40800W
Max. DC voltage	1000V	1000V	1000V
Start voltage	250V	250V	250V
DC nominal voltage	695V	695V	695V
PV voltage range	200V-1000V	200V-1000V	200V-1000V
MPP voltage range (Full load)	480V-800V	520V-800V	570V-800V
Max. input current of the MPP tracker A/tracker B	36A/36A	36A/36A	36A/36A
Max. input short circuit current of the MPP tracker A/tracker B	45A/45A	45A/45A	45A/45A
Number of independent MPP trackers/ strings per MPP tracker	2/4	2/4	2/4
Output (AC)			
Nominal output power	33000W/36660VA	36000W/40000VA	40000W/40000VA
Nominal AC voltage	480V	480V	480V
AC voltage range	422-528VAC	422-528VAC	422-528VAC
Nominal AC grid frequency	60 Hz	60 Hz	60 Hz
AC grid frequency range	59.3-60.5 Hz	59.3-60.5 Hz	59.3-60.5 Hz
Max. output current (cos $\Phi=1$)	44A	48A	48A
Power factor (cos Φ)	>0.99 0.8LG - 0.8LD (0.9LG - 0.9LD at full power)		
Harmonics	<3%	<3%	<3%
Grid connection type	3/NE	3/NE	3/NE
Efficiency			
Max. efficiency	98.8%	98.8%	98.8%
CEC-Weighted Efficiency	98.5%	98.5%	98.5%
MPPT efficiency	99.5%	99.5%	99.5%
Protection Devices			
DC reverse-polarity protection	yes	yes	yes
DC switch for each MPP tracker	yes	yes	yes
AC switch	yes	yes	yes
Input over voltage protection surge arrester	Class II	Class II	Class II
DC insulation measure	yes	yes	yes
AC short circuit protection	yes	yes	yes
Output over voltage protection surge arrester	Class II	Class II	Class II
String fuse type/size	yes(15A/1000VDC)	yes(15A/1000VDC)	yes(15A/1000VDC)
AFCI	yes(Compliant to UL 1699B)	yes(Compliant to UL 1699B)	yes(Compliant to UL 1699B)
String monitor	yes	yes	yes
Anti PID	yes	yes	yes
General Data			
Dimensions (W / H / D) in inch	435/790/265mm 17.1/31.1/10.4inch	435/790/265mm 17.1/31.1/10.4inch	435/790/265mm 17.1/31.1/10.4inch
Weight	50kg/110.2lb	50kg/110.2lb	50kg/110.2lb
Operating temperature range	-25...+60°C/(-13...+ 140°F)	-25...+60°C/(-13...+ 140°F)	-25...+60°C/(-13...+ 140°F)
Noise emission	≤50 dB(A)	≤50 dB(A)	≤50 dB(A)
Relative Humidity	0~100%	0~100%	0~100%
Altitude	≤2000m/6560ft	≤2000m/6560ft	≤2000m/6560ft
Self Consumption night	<6 W(AC Power Supply)	<6 W(AC Power Supply)	<6 W(AC Power Supply)
Topology	Transformerless	Transformerless	Transformerless
Cooling concept	Fan Cooling	Fan Cooling	Fan Cooling
Enclosure	NEMA 3R	NEMA 3R	NEMA 3R
Features			
Display	Graphic	Graphic	Graphic
Interface: RS232/RS485/WIFI/Ethernet/GPRS	yes/yes/opt/opt /opt	yes/yes/opt/opt /opt	yes/yes/opt/opt /opt
Warranty:5years/10years/15years	yes/yes/opt	yes/yes/opt	yes/yes/opt

Certificates and Approvals

UL1741,UL1998,UL 508C,IEEE1547,FCC part 15(class B),CSA C22.2 No.107.1,CSA C22.2 NO.14