


Residential Storage Product

Growatt SP1000/SP2000



Leading - Edge Technology

- ▶ Production in daytime and consumption at night
- ▶ Internal DC switch
- ▶ Ethernet / RS232 / RF / WiFi
- ▶ Easy to add into Grid-tie installed solar system
- ▶ PV and battery power load simultaneously
- ▶ Battery discharging time is programmable
- ▶ Comprehensive Growatt warranty program



GROWATT NEW ENERGY TECHNOLOGY Co.,LTD

A: No.28 Guangming Road, Longteng Community, Shiyan, Baoan District, Shenzhen, P.R.China.

T: + 86 755 2747 1900

F: + 86 755 2749 1460

E: info@ginverter.com

Datasheet	Growatt SP 1000	Growatt SP2000
PV input data		
Recommended input power range	2000W~4000W	3000W~6000W
Max. input current	30A *1	30A *1
Input DC voltage range	100V~580VDC	100V~580VDC
Technical data		
Max. charging and discharging power	1000W	2000W
Full load DC voltage range while charging	100V~450VDC	200V~450VDC
Output voltage range while discharging	150V~400VDC	150V~450VDC
Rated output voltage while discharging	300V	380V
Max. input current (from PV) while charging	10A	10A
Max. output current (to inverter) while discharging	6.7A	10A
Rated output current (to inverter) while discharging	3.3A	5.3A
Number of MPP trackers/strings per MPP tracker	1/3	1/3
Output strings(to inverter)	2	2
Max AC charging power	-	-
Battery data		
Battery type	Lead-acid / Lithium	Lead-acid / Lithium
Recommend battery capacity range	50-100AH	90-200AH
Daily total electricity supply	2~5 kWh	2~9 kWh
Deep of discharge	50% DOD / 80% DOD	50% DOD / 80% DOD
Battery voltage range	46V~58VDC	46V~58VDC
Max charging voltage	58VDC / 57VDC	58VDC / 57VDC
Max charging current	≤23A	≤45A
Max discharging current	≤23A	≤45A
Protection devices		
Over voltage protection	Yes	Yes
Low voltage protection	Yes	Yes
Over current protection	Yes	Yes
Over load protection	Yes	Yes
Output current short protection	Yes	Yes
DC reverse polarity protection	Yes	Yes
Others		
Maximum efficiency	94.0%	94.0%
Dimensions(W/H/D)	482/355/166mm	482/355/166mm
Weight	13.2 kg	13.2 kg
Input grid voltage range (single phase)	230Vac±15%	230Vac±15%
Operating temperature range	0 °C~+40 °C	0 °C~+40 °C
Altitude	2000m	2000m
Cooling concept	Natural	Natural
Environmental protection rating	IP20 (indoor used)	IP20 (indoor used)
Noise emission (typical)	≤25dB	≤25dB
DC connection	H4/MC4 (opt)	H4/MC4 (opt)
Battery connection	Screw terminal	Screw terminal
Display	LED+LCD	LED+LCD
Current sensor:Wired/Wireless	Yes / opt	Yes / opt
Interfaces:RS232 / RF / Ethernet / WiFi	Yes / Yes / opt / opt	Yes / Yes / opt / opt
Warranty	5 years	5 years
Certificates and approvals	CE	CE

Note: *1 Current from PV array, not only to SP, but also to PV inverter.

** It will be available in the near future